




BeneVision N1

Patient Monitor

Connecting the Vision

Key Features

- Palm size 150x102x81cm and Ultralight weight of 950g
- Fully integrated sidestream CO2 module (optional)
- 5.5" High definition screen
- Wide view allowing clear viewing from any angle
- Gesture control touchscreen
- Auto brightness
- 8-hour battery life
- Cross infection control
- IP44 dust/waterproof resistance and a 1.2m drop endurance
- Up to 5 waveforms displayed
- More than 10 critical parameters can be monitored
- Extensive data storage and reliable offline upload
- Flexible transport docking solution for air and ground transport
- Connect to 19" touchscreen display to create expanded bedside monitor
- Multiple mounting solutions
- Wired and wireless communications to Central Stations



ECG

Meet standards of IEC 60601-2-27 and IEC 60601-2-25.

SpO₂

Meet standards of ISO 80601-2-61.

Internal Sidestream CO₂

Meet standard of ISO 80601-2-55.

NIBP

Meet standards of IEC 80601-2-30.

Temperature

Meet standard of ISO 80601-2-56.

IBP

Meet standard of IEC 60601-2-34.



Comply with EN13718-1,
IEC60601-1-12, US
Military MIL-STD-810G



Comply with EN1789



HD Display



Wide View



IP44 Water-
/Dust-proof



Long Battery
Working Time



Easy Operation



Auto Brightness



1.2m Drop
Endurance



Cross Infection
Control